

# Safety Data Sheet Anvil Paints & Coatings, Inc.

# 1220 Roof-Tec White Caulk

#### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** 1220 Roof-Tec White Caulk

Version:

**Identifier 1:** Aggregate Fill Latex Caulk

Identifier 2:1220Chemical Family:Mixture

Product Use: Textured Caulk

**Company Information:** Anvil Paints & Coatings, Inc.

1255 Starkey Road Largo, FL 33771 Phone: (800) 822-6776

Internet Address: www.anvilpaints.com

**Emergency Phone Number:** CHEMTREC

1-800-424-9300

# SECTION 2 HAZARD(S) IDENTIFICATION

Hazard Classification: Health Hazards

N/A

Pictogram(s): N/A

Signal Word: N/A

**Hazard Statements:** N/A

Precautionary Statements: Response

P302+352 - IF ON SKIN: Wash with soap and water.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes.

Remove contact lenses, if present, and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

Disposal

P501 - Dispose of contents/container in accordance with local regulations.

# SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Ingredients

| Chemical Name                | CAS Number  | Concentration (%) |
|------------------------------|-------------|-------------------|
| Titanium Dioxide* (Unbound)  | 13463-67-7  | 0.00 - 10.00%     |
| Water                        | 7732-18-5   | 0.00 - 10.00%     |
| Phthalate Ester              | 68515-42-4  | 0.00 - 10.00%     |
| Calcium Carbonate* (Unbound) | 1317-65-3   | 40.00 - 60.00%    |
| Acrylic Polymer Emulsion     | 122055-81-6 | 40.00 - 60.00%    |

\*The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. When the chemicals are used in applications such as textures or coatings, the chemicals become bound and are not in their hazardous form.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4 FIRST-AID MEASURES

**Inhalation:** If Affected:

Move to fresh air. Restore breathing. Keep quiet and warm.

Consult a physician after significant exposure.

**Skin Contact:** Wash off with soap and plenty of water.

If symptoms persist, call a physician.

**Eye Contact:** Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye(s) wide open while rinsing. If eye irritation persists, consult a specialist.

**Ingestion:** Clean mouth with water and drink plenty of water afterwards.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed:

N/A

**Protection of first-aiders:** Move out of dangerous area.

Consult a physician.

Show this Safety Data Sheet to the doctor in attendance.

**Notes to physician:** Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Suitable extinguishing

media:

Water-based coating. Will not burn under normal circumstances.

Unsuitable extinguishing

media:

N/A

**Specific Precautionary** 

Methods:

Closed containers may explode when exposed to extreme heat. Water may be used to cool

to prevent pressure build-up.

Special protective equipment

for fire-fighters:

In the event of fire, wear self-contained breathing apparatus, if appropriate.

Thermal decomposition may produce toxic fumes of Carbon Monoxide, Carbon Dioxide,

and Hydrogen.

#### **SECTION 6**

# **ACCIDENTAL RELEASE MEASURES**

**Handling Precautions:** Use personal protective equipment.

Deny access to unprotected persons.

Avoid breathing dust/fumes/gas/mist/vapors/spray.

**Environmental precautions:** Do not flush into or allow chemical to enter surface water or sanitary sewer system.

If the product contaminates rivers, lakes, or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.

Cleanup: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, or sawdust).

Keep in suitable, closed containers for disposal.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1940.120).

# SECTION 7 HANDLING AND STORAGE

**Handling Precautions:** Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see Section 8).

Do not get in eyes, on skin, or on clothing. For personal protection, see Section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture

is being used.

Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Storage Requirements: Store in original container.

Keep in a dry and well-ventilated place.

Keep container tightly closed. Observe label precautions.

Store in accordance with local regulations.

#### **SECTION 8**

#### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Exposure Limits**

| Component                | CAS Number  | Basis ** | Value | Exposure Limit(s)* / Form of Exposure |
|--------------------------|-------------|----------|-------|---------------------------------------|
| Titanium Dioxide***      | 13463-67-7  | OSHA     | TWA   | 15 mg/m³ (Total Dust)                 |
| (Unbound)                |             |          |       |                                       |
|                          |             | ACGIH    | TLV   | 10 mg/m³ (Total Dust)                 |
| Calcium Carbonate***     | 471-34-1    | N/A      | N/A   | N/A                                   |
| (Unbound)                |             |          |       |                                       |
| Acrylic Polymer Emulsion | 122055-81-6 | N/A      | N/A   | N/A                                   |
| Phthalate Ester          | 68515-42-4  | N/A      | N/A   | N/A                                   |

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this Safety Data Sheet.

#### \*\*Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminate (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

\*\*\*The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. When the chemicals are used in applications such as textures or coatings, the chemicals become bound and are not in their hazardous form.

# **Engineering Measures:**

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

# Personal Protective Equipment:

# **Respiratory Protection**

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

#### **Hand Protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### **Eye Protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

#### Skin and Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific workplace.

#### **Hygiene Measures**

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the product.

Remove respiratory, and skin/eye protection only after vapors have been cleared from the

Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

# **SECTION 9**

#### PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Paste
Color: White
Relative Density: N/A
pH: 8.5 to 9.0
Odor: Non-descript
Solubility: 100%

Flash Point: Non-flammable VOC: Non-flammable

#### **SECTION 10**

## STABILITY AND REACTIVITY

**Reactivity:** No dangerous reaction known under conditions of normal use.

**Chemical Stability:** The product is chemically stable.

**Hazardous Reactions:** Stable under recommended storage conditions.

**Conditions to Avoid:** 

Extremes of temperature and direct sunlight, as these conditions could lead to pressure

build-up in a sealed container.

# **SECTION 11**

# **TOXICOLOGICAL INFORMATION**

#### Toxicity

| Hazardous Ingredient Name    | Acute or Chronic?    | Oral LD <sub>50</sub> | Dermal LD <sub>50</sub>     | Dermal LC <sub>50</sub> |
|------------------------------|----------------------|-----------------------|-----------------------------|-------------------------|
| Titanium Dioxide* (Unbound)  | Chronic (Inhalation) | > 10,000 mg/kg (rat)  | $\geq 10,000 \text{ mg/kg}$ | NE**                    |
|                              |                      |                       | (hamster)                   |                         |
| Calcium Carbonate* (Unbound) | No                   | 6,450 mg/kg (rat)     | NE**                        | NE**                    |
| Acrylic Polymer Emulsion     | No                   | NE**                  | NE**                        | NE**                    |
| Phthalate Ester              | No                   | NE**                  | NE**                        | NE**                    |

<sup>\*</sup>The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. When the chemicals are used in applications such as textures or coatings, the chemicals become bound and are not in their hazardous form.

\*\*NE = No Evidence

**Irritation:** N/A

**Sensitization:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

#### **SECTION 12**

#### **ECOLOGICAL INFORMATION**

**Environmental Data:** 

This product mixture is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Other Information:

Do not empty into drains; dispose of this material and its container in accordance with state and local regulations. Avoid dispersal of spilled material and runoff, and contact with soil, waterways, drains and sewers.

#### **SECTION 13**

# **DISPOSAL CONSIDERATIONS**

**Disposal Methods:** 

# Waste from Residues

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any federal, state and local authority requirements.

#### Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal in accordance with federal, state and local regulations.

#### **SECTION 14**

# TRANSPORT INFORMATION

DOT:Not dangerous goods.IATA:Not dangerous goods.IMDG:Not dangerous goods.

Non-regulated, not classified as dangerous.

SECTION 15 REGULATORY INFORMATION

Phthalate Ester (68515-42-4) is not listed on the TSCA Inventory or in compliance with a

TSCA Inventory exemption.

**CERCLA Reportable** 

Quantity:

**TSCA list:** 

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable

Quantity:

This material does not contain any components with a section 304 EHS RQ.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III,

Section 302.

**SARA 313:** This material does not contain any chemical components with known CAS numbers that

exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section

313.

Clean Air Act: This product does not contain any hazardous air pollutants (HAP), as defined by the U.S.

Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section

112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

**Ozone-Depletion Potential:** This product neither contains, nor was manufactured with a Class I or Class II ODS as

defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

California Prop 65: WARNING: This product can expose you to chemicals including Titanium Dioxide,

which is known to the State of California to cause cancer when airborne. For more

information, go to www.P65Warnings.ca.gov.

SECTION 16 OTHER INFORMATION

Further Information: This SDS was prepared in accordance with OSHA regulatory standards for Toxic and

Hazardous Substances: 29 CFR 1910.1200

**Disclaimer:** This product is not intended for use in food or pharmaceuticals.

To the best of our knowledge, the information contained herein is accurate. However Anvil Paints & Coatings, Inc. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be handled with care. Although Anvil Paints & Coatings, Inc. has described herein all of the hazards to which we are currently aware, we cannot guarantee

that these are the only hazards which exist.